



MUR

felt wall






# HOW TO SPECIFY


Mur wall-mounted 2-color, double thickness acoustic panels reflect the energy and design of the workspace while removing echo and noise, beautifully.

## 01 SPECS



Tell us about your space, the design, and dimensions.

## 02 SIZE




What size panel does your design call for? Mur comes in 36"H x 24"W or 92"H x 46"W.

## 03 COLORS



Standard. Woodgrains. Customs.  
What's your color? (See page 6)

## 04 MAKE IT YOUR OWN!



Choose one of our patterns or spec your own. (See page 4)

## SHADES by MPS™

-  Signature Series
-  Studio Collaboration
-  The Color Lab

Even more color options with SHADES by MPS. (See page 6)




# PRODUCT SPECIFICATIONS

## STANDARD DIMENSIONS

Standard Small      36"H x 24"W

Standard Large      92"H x 46"W






# PRODUCT SPECIFICATIONS

## DESIGNS


Mur comes in twenty-seven standard patterns, or customize your Mur with your own design.




Bande




Beaded



Cristyl



DNA



Dots



Float



Flock



Jean



Kyte



Inka I



Inka II



Inka III



Llava I




Llava II



Llava III



Lumin II



Matrix



Profyl




Mazon I



Mazon II



Mazon III




Rainfall



Roseau



Santa Fe



Sequence



Tangram



Custom



# TECHNICAL SPECIFICATIONS



## Absorption

Standard: .85 NRC

(subject to mounting conditions)

## Fire Rating

ASTM E84 Class A

## Warranty

Two (2) Years

## VOC

ASTM D5116 Compliant

## Material

PET Felt: 100% polyester fiber

## Maintenance

Vacuum clean to remove dust and debris

## Sustainability

**MPS 9mm Acoustic Panels**  
**MPS LLC**

**Final Assembly:** Plano, Texas, USA  
**Life Expectancy:** 50 Year(s)  
**End of Life Options:** Salvageable/Reusable in its Entirety, Take Back Program (Plano, TX), Recyclable (100%)

**Ingredients:**  
Polyethylene Terephthalate

**Living Building Challenge Criteria:** Compliant

**I-13 Red List:**  
 LBC Red List Free      % Disclosed: 100% at 100ppm  
 LBC Red List Approved      VOC Content: Not Applicable  
 Declared

**I-10 Interior Performance:** CDPH Standard Method v1 2-2017  
**I-14 Responsible Sourcing:** Not Applicable

MPS-0001  
EXP. 01 NOV 2026  
Original Issue Date: 2022

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY  
INTERNATIONAL LIVING FUTURE INSTITUTE™ [living-future.org/declare](http://living-future.org/declare)





# COLORS & WOODGRAINS

MPS offers a range of standard colors, woodgrains, and custom colors with SHADES.

## STANDARD COLORS



## WOODGRAINS



## SHADES by MPS™

Your design world revolves around color, so don't be limited by standard colors and outdated palettes. We've distilled years of testing into a three-tier system that protects print quality and design intent.

\*Some limitations apply. Consult your MPS acoustics expert to discuss your project.

<b>RECOMMENDED</b>	<b>GUIDED CUSTOM</b>	<b>BESPOKE</b>
 <b>Signature Series</b> Proven color. Perfect results.	 <b>Studio Collaboration</b> Your color, guided by our expertise.	 <b>The Color Lab</b> When your color needs to be one-of-a-kind.



# MOUNTING OPTIONS

## TOOLS REQUIRED



Cutting tool



Steel straightedge



Drill




Hole saw



Construction adhesive

## DRY FIT

Before applying adhesive, dry fit the first panel to the wall.




Note: to avoid irregularity, we recommend applying to the top of a baseboard.



## MOUNTING OPTIONS

### APPLY CONSTRUCTION ADHESIVE (RECOMMENDED)



### HOOK Z-CLIPS (ALTERNATIVE)

Determine the desired position of z-clips and screw them into the back of the panel.

