

# Acoustic Panels Cleaning Tips



Recommended Cleaning Steps	
1.	Blot fresh spills as soon as possible with a soft, white, lint-free cloth to avoid the liquid absorbing into the panel material.
2.	If the stain is dry and there is visible soil, use a plastic bristle brush to gently soften the dirt. Avoid excess pressure.
3.	Vacuum the surface thoroughly using a clean dusting brush attachment.
4.	Apply appropriate cleaning solution (see below) to a piece of white, lint-free cloth or sponge. If you use a hand spray application, do not oversoak.
5.	Using the treated cloth, gently blot the stain starting from the outer edge and moving inward.
6.	If required, renew the cleaning cloth. Repeat process until there is no further transfer of the dirt to the cloth.
7.	Once the stain is removed, soak up all remaining cleaning solution with a dry cloth.
8.	Use a clean cloth or sponge soaked in water to remove any residue.
9.	Allow treated surface to air dry

Recommended Cleaning Solutions
<ul style="list-style-type: none"><li>• 50/50 solution of warm water and bleach (5.25% sodium hypochlorite solution)</li></ul>
<ul style="list-style-type: none"><li>• 3% hydrogen peroxide</li></ul>
<ul style="list-style-type: none"><li>• Distilled water (for stain removal only)</li></ul>
<ul style="list-style-type: none"><li>• Avoid cleaners with abrasives such as scouring powders or steel wool.</li></ul>
<ul style="list-style-type: none"><li>• Do not use cleaners that contain ketones, kerosene, or petroleum products.</li></ul>

For Mitigation if Microbial / Viral Contamination
Proper Personal Protective Equipment (PPE) must be worn, i.e. bleach odor respirator, protective eyewear and gloves.
1. Mix equal amount of water and bleach (5.25% sodium hypochlorite solution)
2. Use a hand-spray applicator to mist the surface of product; apply generously, but do not oversoak.
3. Allow treated surface to air dry.